

**Material Safety Data Sheet**

According to 91/155 EC

Printing date 22.05.2003

Reviewed on 22.05.2003

**1 Identification of the substance/preparation and of the company/undertaking****Product details****Trade name: 182**

Application of the substance / the preparation Soldering flux

**Manufacturer/Supplier:**Kester  
515 E. Touhy Ave.  
Des Plaines, IL 60018Tel.(847) 297-1600  
Fax.(847) 390-9338**Further information obtainable from:**

MSDS Coordinator:

Tel. (847) 699-5755

**Information in case of emergency:**




CHEMTREC 24-Hour Emergency Response Telephone Number:


(800) 424-9300

CHEMTREC 24-Hour Emergency Response Telephone Number (Outside US and Canada):

(703) 527-3887

**2 Composition/information on ingredients****Chemical characterization****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol	 Xi,  F; R 11-36-67	50-100%
CAS: 8050-09-7 EINECS: 232-475-7	Rosin	 Xi; R 43	10-25%

**Additional information:** For the wording of the listed risk phrases refer to section 16.**3 Hazards identification****Hazard description:**Xi Irritant  
F Highly flammable**Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Has a narcotizing effect.

R 11 Highly flammable.

R 36 Irritating to eyes.

R 43 May cause sensitisation by skin contact.

R 67 Vapours may cause drowsiness and dizziness.

**4 First-aid measures****After inhalation:** Supply fresh air; consult doctor in case of complaints.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 2)

**Material Safety Data Sheet**

According to 91/155 EC

Printing date 22.05.2003

Reviewed on 22.05.2003

**Trade name: 182**

(Contd. of page 1)

**After eye contact:***Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.***After swallowing:** *Seek medical treatment.***5 Fire-fighting measures****Suitable extinguishing agents:** *CO<sub>2</sub>, sand, extinguishing powder. Do not use water.***For safety reasons unsuitable extinguishing agents:** *Water with full jet***Special hazards caused by the substance, its products of combustion or resulting gases:***In case of fire, the following can be released:**Carbon monoxide (CO)**Carbon dioxide (CO<sub>2</sub>)**Aliphatic aldehydes***Protective equipment:** *Wear self-contained respiratory protective device.***6 Accidental release measures****Person-related safety precautions:** *Ensure adequate ventilation***Measures for environmental protection:** *Do not allow product to reach sewage system or any water course.***Measures for cleaning/collecting:***Absorb with clay, diatomaceous earth, dry sand, or other inert material. Do not use combustible materials such as sawdust. Place in a chemical waste container. Flush residual with water.***7 Handling and storage****Handling:****Information for safe handling:** *Ensure good ventilation/exhaustion at the workplace.***Information about fire - and explosion protection:***Keep ignition sources away - Do not smoke.**Protect against electrostatic charges.***Storage:****Requirements to be met by storerooms and receptacles:** *Store in a cool location.***Information about storage in one common storage facility:** *Store away from oxidizing agents.***Further information about storage conditions:** *Store in cool, dry conditions in well sealed receptacles.***8 Exposure controls/personal protection****Additional information about design of technical facilities:** *No further data; see item 7.***Ingredients with limit values that require monitoring at the workplace:****67-63-0 propan-2-ol**OES *Short-term value: 1250 mg/m<sup>3</sup>, 500 ppm**Long-term value: 999 mg/m<sup>3</sup>, 400 ppm*

(Contd. on page 3)

**Material Safety Data Sheet**

According to 91/155 EC

Printing date 22.05.2003

Reviewed on 22.05.2003

**Trade name: 182**

(Contd. of page 2)

**Additional information:***PEL = Permissible Exposure Limit (OSHA)**REL= Recommended Exposure Limit (NIOSH)**TLV= Threshold Limit Value (ACGIH)**OSHA= Occupational Safety and Health Administration**ACGIH= American Conference of Governmental Industrial Hygienists**NIOSH= National Institute for Occupational Safety and Health***Personal protective equipment:****General protective and hygienic measures:***Keep away from foodstuffs, beverages and feed.**Immediately remove all soiled and contaminated clothing**Wash hands before breaks and at the end of work.**Avoid contact with the eyes and skin.***Respiratory protection:***When ventilation is not sufficient to remove fumes from the breathing zone, a safety approved respirator or self-contained breathing apparatus should be worn.***Protection of hands:***Protective gloves**Material of gloves**Nitrile rubber, NBR**Natural rubber, NR**Penetration time of glove material**The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.***Eye protection:***Safety glasses**Tightly sealed goggles***9 Physical and chemical properties****General Information**

<b>Form:</b>	<i>Liquid</i>
<b>Colour:</b>	<i>Amber coloured</i>
<b>Odour:</b>	<i>Alcohol-like</i>

**Change in condition***Melting point/Melting range: Undetermined.**Boiling point/Boiling range: 82°C***Flash point:** 18°C

(Contd. on page 4)

**Material Safety Data Sheet**

According to 91/155 EC

Printing date 22.05.2003

Reviewed on 22.05.2003

Trade name: 182

(Contd. of page 3)

**Ignition temperature:** 399°C**Danger of explosion:** *Product is not explosive. However, formation of explosive air/vapour mixtures are possible.***Explosion limits:****Lower:** 2.0 Vol %**Upper:** 12.0 Vol %**Vapour pressure at 20°C:** 43.0 hPa**Density at 20°C:** 0.850 g/cm<sup>3</sup>**Solubility in / Miscibility with water at 20°C:** 75 %**10 Stability and reactivity****Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.***Materials to be avoided:** *Strong acids, strong oxidizers.***Dangerous reactions** *No dangerous reactions known.***Dangerous decomposition products:***When heated, the solvents are evaporated and rosin may be thermally degraded to liberate aliphatic aldehydes, acids, and terpenes.***11 Toxicological information****Acute toxicity:****LD/LC50 values relevant for classification:****67-63-0 propan-2-ol**

Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

**Primary irritant effect:***on the skin: Possible local irritation by contact with flux or fumes.**on the eye: Irritating effect.***Sensitization:** *Sensitization possible through skin contact.***Additional toxicological information:***The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:**Irritant***12 Ecological information****General notes:** *Do not allow product to reach ground water, water course or sewage system.*

GB

(Contd. on page 5)

**Material Safety Data Sheet**


According to 91/155 EC

Printing date 22.05.2003

Reviewed on 22.05.2003

Trade name: 182

(Contd. of page 4)

**13 Disposal considerations****Product:****Recommendation***Must not be disposed together with household garbage. Do not allow product to reach sewage system.***Uncleaned packaging:****Recommendation:** *Disposal must be made according to official regulations.***14 Transport information****Land transport ADR/RID (cross-border)****ADR/RID class:** 3 *Flammable liquids.***Danger code (Kemler):** 33**UN-Number:** 1219**Packaging group:** II**Hazard label** 3**Description of goods:** 1219 ISOPROPANOL, mixture**Maritime transport IMDG:****IMDG Class:** 3**UN Number:** 1219**Label** 3**Packaging group:** II**EMS Number:** F-E,S-D**Marine pollutant:** No**Proper shipping name:** ISOPROPANOL, mixture**Air transport ICAO-TI and IATA-DGR:****ICAO/IATA Class:** 3**UN/ID Number:** 1219**Label** 3**Packaging group:** II**Proper shipping name:** ISOPROPANOL, mixture**15 Regulatory information****Labelling according to EU guidelines:****Code letter and hazard designation of product:**

*Xi Irritant*  
*F Highly flammable*

**Hazard-determining components of labelling:***Rosin**propan-2-ol***Risk phrases:***11 Highly flammable.*

(Contd. on page 6)

**Material Safety Data Sheet**

According to 91/155 EC

Printing date 22.05.2003

Reviewed on 22.05.2003

**Trade name: 182**

(Contd. of page 5)

36 Irritating to eyes.  
 43 May cause sensitisation by skin contact.  
 67 Vapours may cause drowsiness and dizziness.

**Safety phrases:**

2 Keep out of the reach of children.  
 24/25 Avoid contact with skin and eyes.  
 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
 37 Wear suitable gloves.  
 46 If swallowed, seek medical advice immediately and show this container or label.

**National regulations:****Technical instructions (air):**

Class	Share in %
III	74.9

**Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

**16 Other information**

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Material Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Material Safety Data Sheet as a source for hazard information.

**Relevant R-phrases**

11 Highly flammable.  
 36 Irritating to eyes.  
 43 May cause sensitisation by skin contact.  
 67 Vapours may cause drowsiness and dizziness.

**Department issuing MSDS:** Product Safety

**Contact:** Heather Holich, MSDS Coordinator

Tel. (847)699-5755