

# SAFETY DATA SHEET (SDS)

according to 1907/2006/EC, Article 31

Printing Date: 07.02.2017

Version number 1

Revision: 07.02.2017

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Trade name: 275 Lead (Pb) Alloy Solder Wire****Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:**

Kester Inc.  
800 West Thorndale Avenue  
Itasca, IL 60143  
Tel 00+1 + 630 616 4000

ITW Specialty Materials (Suzhou) Co., Ltd.  
Hengqiao Road, Wujiang Economic Development Zone  
Suzhou, Jiangsu Province, China 215200  
Tel +86 512 82060807

Kester GmbH  
Ganghofer Strasse 45  
D-82216 Gernlinden Germany  
Tel +49 (0) 8142 4785 0

**Further information obtainable from:** Product Compliance: EHS\_Kester@kester.com**1.4 Emergency telephone number:**

CHEMTREC 24-Hour Emergency Response Telephone Number : (800) 424-9300

CHEMTREC 24-Hour Emergency Response (Outside US &amp; Canada) Telephone Number : (703) 527-3887

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008**

GHS08 health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 1B H360 May damage fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**

GHS07



GHS08

(Continued on page 2)

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 07.02.2017

Version number 1

Revision: 07.02.2017

**Trade name: 275 Lead (Pb) Alloy Solder Wire**

(Continued from page 1)

**Signal word** Danger

**Hazard-determining components of labelling:**

LEAD (Pb)  
Acid Modified Hydrogenated Rosin  
Organic acid

**Hazard statements**

H302+H332 Harmful if swallowed or if inhaled.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H360 May damage fertility or the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P264 Wash thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

Contains lead. Should not be used on surfaces liable to be chewed or sucked by children.  
Restricted to professional users.

**2.3 Other hazards**

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.  
**vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

**Description:** Mixture of substances listed below with nonhazardous additions.

**Chemical components:**

CAS: 7439-92-1 EINECS: 231-100-4	LEAD (Pb) ⚠ Carc. 2, H351; Repr. 1B, H360; STOT RE 2, H373 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	25-40%
	Acid Modified Hydrogenated Rosin ⚠ Skin Sens. 1, H317	1.0-3.0%
	Organic acid ⚠ Acute Tox. 4, H302; Eye Irrit. 2, H319; Skin Sens. 1, H317	0.1-<1%

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

**General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.  
Follow general first aid procedures.

(Continued on page 3)

# SAFETY DATA SHEET (SDS)

according to 1907/2006/EC, Article 31

Printing Date: 07.02.2017

Version number 1

Revision: 07.02.2017

**Trade name: 275 Lead (Pb) Alloy Solder Wire**

(Continued from page 2)

**After inhalation:** Supply fresh air; consult doctor in case of complaints.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:** Rinse opened eye for several minutes under running water.**After swallowing:** Seek immediate medical advice.**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**5.2 Special hazards arising from the substance or mixture** In case of fire, the following can be released:

### 5.3 Advice for firefighters

**Protective equipment:** No special measures required.

## SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation**6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

### 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Thorough dedusting.

Prevent formation of dust.

**Information about fire - and explosion protection:** No special measures required.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

**Requirements to be met by storerooms and receptacles:** Store in a cool location.**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:** Keep container tightly sealed.**7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

**Additional information about design of technical facilities:** No further data; see item 7.

### 8.1 Control parameters

**Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Continued on page 4)

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 07.02.2017

Version number 1

Revision: 07.02.2017

**Trade name: 275 Lead (Pb) Alloy Solder Wire**

(Continued from page 3)

**8.2 Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.

**Respiratory protection:**

Not necessary if room is well-ventilated.  
Use suitable respiratory protective device in case of insufficient ventilation.

**Protection of hands:**



Protective gloves

**Material of gloves**

Nitrile rubber, NBR  
Natural rubber, NR

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**



Safety Glasses with Side Shields Required

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**General Information**

**Appearance:**

<b>Form:</b>	Solid
<b>Colour:</b>	Silver grey
<b>Odour:</b>	Mild
<b>pH-value:</b>	Not applicable.

**Change in condition**

<b>Melting point/freezing point:</b>	183 °C Undetermined.
<b>Initial boiling point and boiling range:</b>	>999 °C

**Flash point:** NA °C

**Flammability (solid, gas):** Not determined.

**Auto-ignition temperature:** Product is not selfigniting.

**Explosive properties:** Product does not present an explosion hazard.

**Vapour pressure:** Not applicable.

**Density:** Not determined.

**Vapour density:** Not applicable.

(Continued on page 5)

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 07.02.2017

Version number 1

Revision: 07.02.2017

**Trade name: 275 Lead (Pb) Alloy Solder Wire**

(Continued from page 4)

**Solubility in / Miscibility with water:** Insoluble.

**Solvent content:**

**Organic solvents:** 0.0 %

**Solids content:** 100.0 %

**SECTION 10: Stability and reactivity**

- 10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid** No further relevant information available.
- 10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

**Acute toxicity**

Harmful if swallowed or if inhaled.

**LD/LC50 values relevant for classification:**

**CAS: 7439-92-1 LEAD (Pb)**

Oral	LD50	500 mg/kg (ATE)
Inhalative	LC50/4 h	1.5 mg/l (ATE)

**Rosin**

Oral	LD50	> 4000 mg/kg (Rat)
Dermal	LD50	>2500 mg/kg (rabbit)

**Primary irritant effect:**

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation**

May cause an allergic skin reaction.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity**

Suspected of causing cancer.

**Reproductive toxicity**

May damage fertility or the unborn child.

**STOT-single exposure** Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Aquatic toxicity:** No further relevant information available.

(Continued on page 6)

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 07.02.2017

Version number 1

Revision: 07.02.2017

**Trade name: 275 Lead (Pb) Alloy Solder Wire**

(Continued from page 5)

**Additional ecological information:**

**General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

**12.5 Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

**14.1 UN-Number**

IMDG, IATA Void

**14.2 UN proper shipping name**

ADR, ADN, IMDG, IATA Void

**14.3 Transport hazard class(es)**

**ADR, ADN, IMDG, IATA**

Class Void

**14.4 Packing group**

ADR, IMDG, IATA Void

**14.5 Environmental hazards:**

Not applicable.

**14.6 Special precautions for user**

Not applicable.

**14.7 Transport in bulk according to Annex II of Marpol**

and the IBC Code Not applicable.

**UN "Model Regulation":**

Void

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

All ingredients are listed on the following Government Inventories:

China: Inventory of Existing Chemical Substances in China (IECSC)

Korea: Korea Existing Chemicals List (ECL)

Europe: European Inventory of Existing Commercial Chemical Substances (EINECS)

Japan: Inventory of Existing and New Chemical Substances (ENCS)

Philippines: Philippine Inventory of Chemicals and Chemical Substances (PICCS)

USA: TSCA (Toxic Substances Control Act) TSCA Inventory of Chemical Substances

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Continued on page 7)

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 07.02.2017

Version number 1

Revision: 07.02.2017

**Trade name: 275 Lead (Pb) Alloy Solder Wire**

(Continued from page 6)

**Hazard pictograms**

GHS07 GHS08

**Signal word** Danger**Hazard-determining components of labelling:**

LEAD (Pb)

Acid Modified Hydrogenated Rosin

Organic acid

**Hazard statements**

H302+H332 Harmful if swallowed or if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P302+P352 IF ON SKIN: Wash with plenty of water.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Directive 2012/18/EU****Named dangerous substances - ANNEX I** None of the ingredients is listed.**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 63**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Safety Data Sheet (SDS) relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Safety Data Sheet (SDS) as a source for hazard information.

**Department issuing SDS:** Product Compliance / EHS Department**Contact:** EHS\_Kester@kester.com**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Continued on page 8)

## SAFETY DATA SHEET (SDS)

according to 1907/2006/EC, Article 31

Printing Date: 07.02.2017

Version number 1

Revision: 07.02.2017

**Trade name: 275 Lead (Pb) Alloy Solder Wire**

(Continued from page 7)

EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
WHMIS: Workplace Hazardous Materials Information System (Canada)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
Acute Tox. 4: Acute toxicity – Category 4  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Skin Sens. 1: Skin sensitisation – Category 1  
Carc. 2: Carcinogenicity – Category 2  
Carc. 2: Carcinogenicity – Category 2  
Repr. 1B: Reproductive toxicity – Category 1B  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

**\* Data compared to the previous version altered.**

GB