

# SAFETY DATA SHEET (SDS)

according to 1907/2006/EC, Article 31

Printing Date: 16.10.2017

Version number 8

Revision: 16.10.2017

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

**1.1 Trade name: 984 Soldering Flux****1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

Kester Inc.  
800 West Thorndale Avenue  
Itasca, IL 60143  
Tel 00+1 + 630 616 4000

ITW Specialty Materials (Suzhou) Co., Ltd.  
Hengqiao Road, Wujiang Economic Development Zone  
Suzhou, Jiangsu Province, China 215200  
Tel +86 512 82060807

Kester GmbH  
Ganghofer Strasse 45  
D-82216 Gernlinden Germany  
Tel +49 (0) 8142 4785 0

**Further information obtainable from:** Product Compliance: EHS\_Kester@kester.com**1.4 Emergency telephone number:**

CHEMTREC 24-Hour Emergency Response Telephone Number : (800) 424-9300

CHEMTREC 24-Hour Emergency Response (Outside US &amp; Canada) Telephone Number : (703) 527-3887

## SECTION 2: Hazards identification

**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**

GHS02 GHS07

**Signal word** Danger**Hazard-determining components of labelling:**

Isopropanol

(Continued on page 2)

GB

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 16.10.2017

Version number 8

Revision: 16.10.2017

Trade name: **984 Soldering Flux**

(Continued from page 1)

**Hazard statements**

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

Contains Halogenated organic diol. May produce an allergic reaction.

**2.3 Other hazards**

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

**Description:** Mixture of substances listed below with nonhazardous additions.

**Chemical components:**

CAS: 67-63-0 EINECS: 200-661-7	Isopropanol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	85-100%
Trade Secret	Proprietary Organic Acids Acute Tox. 4, H302; Acute Tox. 4, H312; Eye Irrit. 2, H319	1-3%
Trade Secret	Halogenated organic diol Acute Tox. 4, H302; Eye Irrit. 2, H319; Skin Sens. 1B, H317	0.1- 1%

**SVHC**

This product does not contain any Substance of Very High Concern (SVHC) on the European Chemicals Agency (ECHA) candidate list.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

**General information:** Follow general first aid procedures.

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:**

If symptoms persist consult doctor.

Seek immediate medical advice.

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Continued on page 3)

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 16.10.2017

Version number 8

Revision: 16.10.2017

Trade name: 984 Soldering Flux

**4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

(Continued from page 2)

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing agents:** CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**5.2 Special hazards arising from the substance or mixture**

Nitrogen oxides (NOx)

In case of fire, the following can be released:

**5.3 Advice for firefighters**

**Protective equipment:** No special measures required.

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

**6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling** Prevent formation of aerosols.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:** Store in a cool location.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

**7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

**Additional information about design of technical facilities:** No further data; see item 7.

**8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

**CAS: 67-63-0 Isopropanol**

PEL	Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm
	Long-term value: 980 mg/m <sup>3</sup> , 400 ppm

(Continued on page 4)

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 16.10.2017

Version number 8

Revision: 16.10.2017

**Trade name: 984 Soldering Flux**

(Continued from page 3)

TWA	Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
WEL	Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm Long-term value: 999 mg/m <sup>3</sup> , 400 ppm

**8.2 Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.

**Respiratory protection:**

Not necessary if room is well-ventilated.  
Use suitable respiratory protective device in case of insufficient ventilation.

**Protection of hands:**



Protective gloves

**Material of gloves**

Nitrile rubber, NBR  
Natural rubber, NR

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**



Safety Glasses with Side Shields Required

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**General Information**

**Appearance:**

**Form:** Liquid  
**Colour:** Colourless  
**Odour:** Alcohol-like  
**pH-value:** Not determined.

**Change in condition**

**Melting point/freezing point:** Undetermined.

**Flash point:** 18°C

**Ignition temperature:** 399°C

**Auto-ignition temperature:** Product is not selfigniting.

**Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Continued on page 5)

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 16.10.2017

Version number 8

Revision: 16.10.2017

Trade name: 984 Soldering Flux

(Continued from page 4)

**Explosion limits:**  
**Lower:** 2Vol %  
**Upper:** 12Vol %  
**Vapour pressure at 20°C:** 43hPa  
**Density at 20°C:** 0.8g/cm<sup>3</sup>  
**Solubility in / Miscibility with water at 20°C:** 1g/l  
**Viscosity:**  
**Dynamic at 20°C:** 2.43mPas  
**Solvent content:**  
**Organic solvents:** 97.7%  
**Solids content:** 2.3%

**SECTION 10: Stability and reactivity**

**10.1 Reactivity** No further relevant information available.  
**10.2 Chemical stability**  
**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.  
**10.3 Possibility of hazardous reactions** No dangerous reactions known.  
**10.4 Conditions to avoid** No further relevant information available.  
**10.5 Incompatible materials:** Strong acids, strong oxidizers.  
**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**  
**Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:**

**CAS: 67-63-0 Isopropanol**

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

**Primary irritant effect:**  
**Skin corrosion/irritation** Based on available data, the classification criteria are not met.  
**Serious eye damage/irritation**  
 Causes serious eye irritation.  
**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.  
**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**  
**Germ cell mutagenicity** Based on available data, the classification criteria are not met.  
**Carcinogenicity** Based on available data, the classification criteria are not met.  
**Reproductive toxicity** Based on available data, the classification criteria are not met.  
**STOT-single exposure**  
 May cause drowsiness or dizziness.  
**STOT-repeated exposure** Based on available data, the classification criteria are not met.

(Continued on page 6)

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 16.10.2017

Version number 8

Revision: 16.10.2017

Trade name: 984 Soldering Flux

**Aspiration hazard** Based on available data, the classification criteria are not met.

(Continued from page 5)

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Aquatic toxicity:** No further relevant information available.

**Additional ecological information:**

**General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

**12.5 Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Recommendation**

Disposal must be made according to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

**Recommended cleansing agents:** Water, if necessary together with cleansing agents.

**SECTION 14: Transport information**

**14.1 UN-Number**

IMDG, IATA

UN1219

**14.2 UN proper shipping name**

ADR

IMDG, IATA

1219 ISOPROPANOL (ISOPROPYL ALCOHOL) mixture  
ISOPROPANOL (ISOPROPYL ALCOHOL) mixture

**14.3 Transport hazard class(es)**

ADR, IMDG, IATA



**Class**

3 Flammable liquids.

**Label**

3

**14.4 Packing group**

ADR, IMDG, IATA

II

**14.5 Environmental hazards:**

**Marine pollutant:**

No

**14.6 Special precautions for user**

Not applicable.

**Danger code (Kemler):**

33

**EMS Number:**

F-E,S-D

**Stowage Category**

B

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

(Continued on page 7)

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 16.10.2017

Version number 8

Revision: 16.10.2017

Trade name: 984 Soldering Flux

(Continued from page 6)

**Transport/Additional information:**

**ADR**  
**Limited quantities (LQ)** 1L  
**Excepted quantities (EQ)** Code: E2  
 Maximum net quantity per inner packaging: 30 ml  
**Transport category** 2  
**Tunnel restriction code** D/E

**IMDG**  
**Limited quantities (LQ)** 1L  
**Excepted quantities (EQ)** Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 500 ml  
**UN "Model Regulation":** UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL) MIXTURE, 3, II

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

All ingredients are listed on the following Government Inventories:

- China: Inventory of Existing Chemical Substances in China (IECSC)
- Korea: Korea Existing Chemicals List (ECL)
- Europe: European Inventory of Existing Commercial Chemical Substances (EINECS)
- Japan: Inventory of Existing and New Chemical Substances (ENCS)
- Philippines: Philippine Inventory of Chemicals and Chemical Substances (PICCS)
- USA: TSCA (Toxic Substances Control Act) TSCA Inventory of Chemical Substances

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**



GHS02 GHS07

**Signal word** Danger

**Hazard-determining components of labelling:**

Isopropanol

**Hazard statements**

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

(Continued on page 8)



## SAFETY DATA SHEET (SDS)

according to 1907/2006/EC, Article 31

Printing Date: 16.10.2017

Version number 8

Revision: 16.10.2017

**Trade name: 984 Soldering Flux**

(Continued from page 7)

P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Safety Data Sheet (SDS) relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Safety Data Sheet (SDS) as a source for hazard information.

**Department issuing SDS:** Product Compliance / EHS Department

**Contact:** EHS\_Kester@kester.com

**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* **Data compared to the previous version altered.**