

# SAFETY DATA SHEET (SDS)

according to 1907/2006/EC, Article 31

Printing Date: 28.11.2017

Version number 11

Revision: 28.11.2017

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Trade name: 186-18 Soldering Flux

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

### 1.3 Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

Kester Inc.  
800 West Thorndale Avenue  
Itasca, IL 60143  
Tel 00+1 + 630 616 4000

ITW Specialty Materials (Suzhou) Co., Ltd.  
Hengqiao Road, Wujiang Economic Development Zone  
Suzhou, Jiangsu Province, China 215200  
Tel +86 512 82060807

Kester GmbH  
Ganghofer Strasse 45  
D-82216 Gernlinden Germany  
Tel +49 (0) 8142 4785 0

Further information obtainable from: Product Compliance: EHS\_Kester@kester.com

### 1.4 Emergency telephone number:

CHEMTREC 24-Hour Emergency Response Telephone Number : (800) 424-9300

CHEMTREC 24-Hour Emergency Response (Outside US & Canada) Telephone Number : (703) 527-3887

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.  
Skin Sens. 1 H317 May cause an allergic skin reaction.  
STOT SE 3 H336 May cause drowsiness or dizziness.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

#### Hazard pictograms



GHS02 GHS07

Signal word Danger

(Continued on page 2)

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 28.11.2017

Version number 11

Revision: 28.11.2017

**Trade name: 186-18 Soldering Flux**

(Continued from page 1)

**Hazard-determining components of labelling:**

Isopropanol  
Modified Rosin

**Hazard statements**

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash thoroughly after handling.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3 Other hazards**





**Results of PBT and vPvB assessment**

**PBT:** Not applicable.  
**vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

**Description:** Mixture of substances listed below with nonhazardous additions.

**Chemical components:**

CAS: 67-63-0 EINECS: 200-661-7	Isopropanol	 Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336	70-85%
Trade Secret	Modified Rosin	 Skin Sens. 1, H317	5-25%
CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol	 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	3-5%

**SVHC**

This product does not contain any Substance of Very High Concern (SVHC) on the European Chemicals Agency (ECHA) candidate list.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

**General information:** Follow general first aid procedures.

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** Seek immediate medical advice.

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## SAFETY DATA SHEET (SDS)

according to 1907/2006/EC, Article 31

Printing Date: 28.11.2017

Version number 11

Revision: 28.11.2017

Trade name: 186-18 Soldering Flux

(Continued from page 2)

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

**Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**For safety reasons unsuitable extinguishing agents:** Water with full jet

**5.2 Special hazards arising from the substance or mixture** In case of fire, the following can be released:

#### 5.3 Advice for firefighters

**Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

**6.2 Environmental precautions:** No special measures required.

#### 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

#### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

**7.1 Precautions for safe handling** Prevent formation of aerosols.

#### Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Storage:

**Requirements to be met by storerooms and receptacles:** Store in a cool location.

**Information about storage in one common storage facility:** Not required.

#### Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

**7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

**Additional information about design of technical facilities:** No further data; see item 7.

#### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

**CAS: 67-63-0 Isopropanol**

PEL Short-term value: 1225 mg/m<sup>3</sup>, 500 ppm

Long-term value: 980 mg/m<sup>3</sup>, 400 ppm

(Continued on page 4)

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 28.11.2017

Version number 11

Revision: 28.11.2017

**Trade name: 186-18 Soldering Flux**

(Continued from page 3)

TWA	Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
WEL	Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm Long-term value: 999 mg/m <sup>3</sup> , 400 ppm

**8.2 Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

**Respiratory protection:**

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

**Protection of hands:**



Protective gloves

**Material of gloves**

Nitrile rubber, NBR

Natural rubber, NR

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**



Safety Glasses with Side Shields Required

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**General Information**

**Appearance:**

**Form:** Liquid

**Colour:** Amber coloured

**Odour:** Alcohol-like

**pH-value:** Not determined.

**Change in condition**

**Melting point/freezing point:** Undetermined.

**Initial boiling point and boiling range:** 82 °C

**Flash point:** 12 °C

**Ignition temperature:** 399 °C

**Auto-ignition temperature:** Product is not selfigniting.

(Continued on page 5)

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 28.11.2017

Version number 11

Revision: 28.11.2017

Trade name: 186-18 Soldering Flux

(Continued from page 4)

<b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<b>Explosion limits:</b>	
Lower:	2 Vol %
Upper:	12 Vol %
<b>Vapour pressure at 20 °C:</b>	43 hPa
<b>Density at 20 °C:</b>	0.83 g/cm <sup>3</sup>
<b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
<b>Solvent content:</b>	
Organic solvents:	82.1 %
Water:	0.0 %
<b>Solids content:</b>	17.9 %

**SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**  
**Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:**

**CAS: 67-63-0 Isopropanol**

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

**Modified Rosin**

Oral	LD50	>4,000 mg/kg (Rat)
Dermal	LD50	>2,500 mg/kg (rabbit)

- Primary irritant effect:**
- Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- Serious eye damage/irritation**  
Causes serious eye irritation.
- Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- Carcinogenicity** Based on available data, the classification criteria are not met.
- Reproductive toxicity** Based on available data, the classification criteria are not met.

(Continued on page 6)

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 28.11.2017

Version number 11

Revision: 28.11.2017

Trade name: 186-18 Soldering Flux

(Continued from page 5)

**STOT-single exposure**

May cause drowsiness or dizziness.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Aquatic toxicity:** No further relevant information available.

**Additional ecological information:**

**General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**12.5 Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

**14.1 UN-Number**

**IMDG, IATA** UN1219

**14.2 UN proper shipping name**

**ADR** 1219 ISOPROPANOL (ISOPROPYL ALCOHOL) mixture  
**IMDG, IATA** ISOPROPANOL (ISOPROPYL ALCOHOL) mixture

**14.3 Transport hazard class(es)**

**ADR, IMDG, IATA**



**Class**

3 Flammable liquids.

**Label**

3

**14.4 Packing group**

**ADR, IMDG, IATA** II

**14.5 Environmental hazards:**

Not applicable.

**14.6 Special precautions for user**

Not applicable.

**Danger code (Kemler):**

33

**EMS Number:**

F-E,S-D

**Stowage Category**

B

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

(Continued on page 7)

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 28.11.2017

Version number 11

Revision: 28.11.2017

Trade name: 186-18 Soldering Flux

(Continued from page 6)

**Transport/Additional information:**

<b>ADR</b>	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml
<b>Transport category</b>	2
<b>Tunnel restriction code</b>	D/E
<b>IMDG</b>	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<b>UN "Model Regulation":</b>	UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL) MIXTURE, 3, II

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

All ingredients are listed on the following Government Inventories:

- China: Inventory of Existing Chemical Substances in China (IECSC)
- Korea: Korea Existing Chemicals List (ECL)
- Europe: European Inventory of Existing Commercial Chemical Substances (EINECS)
- Japan: Inventory of Existing and New Chemical Substances (ENCS)
- Philippines: Philippine Inventory of Chemicals and Chemical Substances (PICCS)
- USA: TSCA (Toxic Substances Control Act) TSCA Inventory of Chemical Substances

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**



GHS02 GHS07

**Signal word** Danger

**Hazard-determining components of labelling:**

Isopropanol  
Modified Rosin

**Hazard statements**

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Continued on page 8)

**SAFETY DATA SHEET (SDS)**  
according to 1907/2006/EC, Article 31

Printing Date: 28.11.2017

Version number 11

Revision: 28.11.2017

**Trade name: 186-18 Soldering Flux**

(Continued from page 7)

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Directive 2012/18/EU****Named dangerous substances - ANNEX I** None of the ingredients is listed.**Seveso category** P5c FLAMMABLE LIQUIDS**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Safety Data Sheet (SDS) relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Safety Data Sheet (SDS) as a source for hazard information.

**Department issuing SDS:** Product Compliance / EHS Department**Contact:** EHS\_Kester@kester.com**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

**\* Data compared to the previous version altered.**