

Safety Data Sheet
acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/27/2017

Version number 8

Reviewed on 10/27/2017

1 Identification

Trade name: TSF-6750 Tacky Soldering Flux
Relevant identified uses of the substance or mixture and uses advised against
 No further relevant information available.

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Kester Inc.
 800 West Thorndale Avenue
 Itasca, IL 60143 USA
 Tel (630) 616-4000
 Tel International 00 1 630 616-4000

ITW Specialty Materials (Suzhou) Co., Ltd.
 Heng Qiao Road
 Wujiang Economic Development Zone
 Suzhou, Jiangsu 215200 China
 Tel +86 512 82060808

Kester GmbH
 Ganghofer Strasse 45
 D-82216 Gernlinden Germany
 Tel +49 (0) 8142 4785 0

Information department: Product Compliance: EHS_Kester@kester.com

Emergency telephone number:

CHEMTREC 24-Hour Emergency Response Telephone Number : (800) 424-9300
 CHEMTREC 24-Hour Emergency Response (Outside US & Canada) Telephone Number : (703) 527-3887

2 Hazard(s) identification

Classification of the substance or mixture



Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



Acute Tox. 4 H302 Harmful if swallowed.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Acute 3 H402 Harmful to aquatic life.
 Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)
US

Safety Data Sheet
acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/27/2017

Version number 8

Reviewed on 10/27/2017

Trade name: TSF-6750 Tacky Soldering Flux

(Contd. of page 1)

Hazard pictograms



GHS07 GHS08

Signal word Warning

Hazard-determining components of labeling:

2-Phenoxyethanol
Modified Rosin
Heterocyclic derivative

Hazard statements

H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H361 Suspected of damaging fertility or the unborn child.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.
P302+P352 If on skin: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 2
Fire = 1
Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = *2
Fire = 1
Reactivity = 0

Other hazards


Results of PBT and vPvB assessment

PBT: Not applicable.
vPvB: Not applicable.

3 Composition/information on ingredients

Description: Mixture of the substances listed below with nonhazardous additions.

CAS No.	Description	% Range
CAS: 122-99-6	2-Phenoxyethanol	25-40%

 Acute Tox. 4, H302; Eye Irrit. 2A, H319

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/27/2017

Version number 8

Reviewed on 10/27/2017

Trade name: TSF-6750 Tacky Soldering Flux

(Contd. of page 2)

Trade Secret	Modified Rosin	⚠ Skin Sens. 1, H317	10-25%
Trade Secret	Heterocyclic derivative	⚠ Acute Tox. 3, H301 ⚠ Repr. 2, H361 ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335 ⚠ Aquatic Acute 2, H401	3-5%
Trade Secret	Proprietary solvent	⚠ Skin Irrit. 2, H315 ⚠ Eye Irrit. 2B, H320	3-5%
CAS: 75-75-2	Alkyl Sulfonic acid	⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318	1-3%

4 First-aid measures

Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Follow general first aid procedures.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Seek immediate medical advice.

Information for doctor:

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture In case of fire, the following can be released:

Advice for firefighters

Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:

CAS: 122-99-6	2-Phenoxyethanol	1.5 ppm
	Heterocyclic derivative	0.97 mg/m ³
CAS: 75-75-2	Alkyl Sulfonic acid	0.99 mg/m ³

PAC-2:

CAS: 122-99-6	2-Phenoxyethanol	16 ppm
---------------	------------------	--------

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/27/2017

Version number 8

Reviewed on 10/27/2017

Trade name: TSF-6750 Tacky Soldering Flux

(Contd. of page 3)

	Heterocyclic derivative	11 mg/m ³
CAS: 75-75-2	Alkyl Sulfonic acid	11 mg/m ³
PAC-3:		
CAS: 122-99-6	2-Phenoxyethanol	97 ppm
	Heterocyclic derivative	64 mg/m ³
CAS: 75-75-2	Alkyl Sulfonic acid	65 mg/m ³

7 Handling and storage

Handling:

Precautions for safe handling Prevent formation of dust.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information:

PEL = Permissible Exposure Limit (OSHA)

TLV= Threshold Limit Value (ACGIH)

OSHA= Occupational Safety and Health Administration

ACGIH= American Conference of Governmental Industrial Hygienists

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

When ventilation is not sufficient to remove fumes from the breathing zone, a safety approved respirator or self-contained breathing apparatus should be worn.

Filter AX

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/27/2017

Version number 8

Reviewed on 10/27/2017

Trade name: TSF-6750 Tacky Soldering Flux

(Contd. of page 4)

Protection of hands:



Protective gloves

Material of gloves:

Nitrile rubber, NBR

Natural rubber, NR

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form:	Viscous
Color:	Colorless
Odor:	Mild
pH-value:	Not applicable.

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	244 °C (471.2 °F)

Flash point: 121 °C (249.8 °F)

Flammability (solid, gaseous): Not determined.

Ignition temperature: 535 °C (995 °F)

Auto igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Vapor pressure: Not applicable.

Density: Not determined.

Vapor density: Not applicable.

Solubility in / Miscibility with

Water: Insoluble.

Solvent content:

Organic solvents: 36.9 %

Solids content: 61.5 %

Safety Data Sheet
acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/27/2017

Version number 8

Reviewed on 10/27/2017

Trade name: TSF-6750 Tacky Soldering Flux

(Contd. of page 5)

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: Strong acids, strong oxidizers.

Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

CAS: 122-99-6 2-Phenoxyethanol

Oral	LD50	1,260 mg/kg (rat)
------	------	-------------------

Dermal	LD50	5,000 mg/kg (rabbit)
--------	------	----------------------

Modified Rosin

Oral	LD50	>4,000 mg/kg (Rat)
------	------	--------------------

Dermal	LD50	>2,500 mg/kg (rabbit)
--------	------	-----------------------

Heterocyclic derivative

Oral	LD50	100 mg/kg (ATE)
------	------	-----------------

Primary irritant effect:

on the skin: No irritant effect.

on the eye: Irritating effect.

Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

Carcinogenic categories

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Ecotoxicological effects:

Remark: Harmful to fish

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/27/2017

Version number 8

Reviewed on 10/27/2017

Trade name: TSF-6750 Tacky Soldering Flux

(Contd. of page 6)

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

13 Disposal considerations

Waste treatment methods

Recommendation:

Disposal must be made according to official regulations.
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number

DOT, ADR, ADN, IMDG, IATA Not applicable

UN proper shipping name

DOT, ADR, ADN Not applicable

IMDG, IATA Not applicable

Not regulated

Transport hazard class(es)

DOT, ADR, ADN, IMDG, IATA

Class Not applicable

Packing group

DOT, IMDG, IATA Not applicable

Special precautions for user Not applicable.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

UN "Model Regulation": Not applicable

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

All ingredients are listed on the following Government Inventories:

China: Inventory of Existing Chemical Substances in China (IECSC)

Korea: Korea Existing Chemicals List (ECL)

Europe: European Inventory of Existing Commercial Chemical Substances (EINECS)

Japan: Inventory of Existing and New Chemical Substances (ENCS)

Philippines: Philippine Inventory of Chemicals and Chemical Substances (PICCS)

USA: TSCA (Toxic Substances Control Act) TSCA Inventory of Chemical Substances

USA The following information relates to product regulation specific to the USA.

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/27/2017

Version number 8

Reviewed on 10/27/2017

Trade name: TSF-6750 Tacky Soldering Flux

(Contd. of page 7)

SARA (Superfund Amendments and Reauthorization Act)

Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

CAS: 122-99-6 | 2-Phenoxyethanol

Proprietary solvent

TSCA new (21st Century Act) (Substances not listed)

California Proposition 65

Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

Carcinogenic categories

EPA (Environmental Protection Agency)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

CANADA:

Workplace Hazardous Materials Identification (WHMIS):

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR) and the Safety Data Sheet (SDS) contains all of the information required by the CPR.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS07 GHS08

Signal word Warning

Hazard-determining components of labeling:

2-Phenoxyethanol
Modified Rosin
Heterocyclic derivative

Hazard statements

H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H361 Suspected of damaging fertility or the unborn child.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.
P302+P352 If on skin: Wash with plenty of water.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/27/2017

Version number 8

Reviewed on 10/27/2017

Trade name: TSF-6750 Tacky Soldering Flux

(Contd. of page 8)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Material Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Material Safety Data Sheet as a source for hazard information.

Department issuing Safety Data Sheet (SDS): Product Compliance / EHS Department

Contact: EHS_Kester@kester.com

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* **Data compared to the previous version altered.**