

1: PRODUCT AND COMPANY IDENTIFICATION

Trade name: FL250D Solder Paste Sn63Pb37 Alloy

Article number: P2-10-FL250D

Application of the substance / the preparation: Solder paste

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Kester Inc.
800 West Thorndale Avenue
Itasca, IL 60143
Tel (630) 616-4000

ITW Specialty Materials (Suzhou) Co., Ltd.
Heng Qiao Road
Wujiang Economic Development Zone
Suzhou, Jiangsu 215200 China
Tel +86 512 82060808

Information department:

Product Compliance: EHS_Kester@kester.com

1.4 Emergency telephone number:

CHEMTREC 24-Hour Emergency Response Telephone Number : (800) 424-9300

CHEMTREC 24-Hour Emergency Response (Outside US & Canada) Telephone Number : (703) 527-3887

2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS08 Health hazard

Repr. 1B H360 May damage fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labeled according to the CLP regulation.

Hazard pictograms



GHS07 GHS08

Signal word Danger

Hazard-determining components of labeling:

LEAD (Pb)
Rosin
Rosin

Trade name: FL250D Solder Paste Sn63Pb37 Alloy

(Contd. of page 1)

Halogenated organic diol

Hazard statements

Harmful if swallowed.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

In case of inadequate ventilation wear respiratory protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

IF ON SKIN: Wash with plenty of water.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard description:**WHMIS Symbols****Classification system:****NFPA ratings (scale 0 - 4)**

Health = 1
Fire = 1
Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = *1
Fire = 1
Reactivity = 0

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

3: COMPOSITION OF MIXTURE

Description: Mixture of the substances listed below with nonhazardous additions.

CAS No.	Description	% Range
CAS: 7440-31-5 EINECS: 231-141-8	TIN (Sn)	55-70%
CAS: 7439-92-1 EINECS: 231-100-4	LEAD (Pb) ⚠ Carc. 2, H351; Repr. 1B, H360; STOT RE 2, H373 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	25-40%
	Rosin ⚠ Skin Sens. 1, H317	
CAS: 55934-93-5 EINECS: 259-910-3	[(butoxymethylethoxy)methylethoxy]propan-1-ol	1.0-3.0%
CAS: 143-24-8 EINECS: 205-594-7	bis(2-(2-methoxyethoxy)ethyl) ether ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	1.0-3.0%

(Contd. on page 3)

Trade name: FL250D Solder Paste Sn63Pb37 Alloy

(Contd. of page 2)

	Rosin ⚠ Skin Sens. 1, H317	
CAS: 64742-30-9 EINECS: 265-130-4	Distillates (petroleum), chemically neutralized middle ⚠ Carc. 1B, H350	≤1.0%
	Halogenated organic diol ⚠ Acute Tox. 4, H302; Eye Irrit. 2A, H319; Skin Sens. 1B, H317	

Additional information: Solder powder is typically 85-92% of the solder paste composition.

4: FIRST AID MEASURES

4.1 Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Follow general first aid procedures.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Nitrogen oxides (NO_x)

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO₂)

Aliphatic aldehydes

5.3 Advice for firefighters

Protective equipment: Wear self-contained respiratory protective device.

6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Scoop up paste and deposit in appropriate containers.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.



SAFETY DATA SHEET (SDS)
According to 1907/2006/EC, Article 31

Version number 10

Reviewed on 12/01/2015

Trade name: FL250D Solder Paste Sn63Pb37 Alloy

(Contd. of page 3)

7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Open and handle receptacle with care.
Prevent formation of aerosols.

Wash hands after handling paste and before eating or smoking. Care should be taken to remove paste from under fingernails.

Information about protection against explosions and fires: Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.
Store at or near 5°C in a dry location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed.

7.3 Specific end use(s)

Shelf life is 6 months from date of manufacture when stored at 0-10 °C (32-50°F).
No further relevant information available.

8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Additional information about design of technical systems: No further data; see item 7.

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

7440-31-5 TIN (Sn)

PEL	Long-term value: 2 mg/m ³ metal
REL	Long-term value: 2 mg/m ³
TLV	Long-term value: 2 mg/m ³ metal

7439-92-1 LEAD (Pb)

PEL	Long-term value: 0.05* mg/m ³ *see 29 CFR 1910.1025
REL	Long-term value: 0.05* mg/m ³ *8-hr TWA, excl. lead arsenate; See PocketGuideApp.C
TLV	Long-term value: 0.05* mg/m ³ *and inorganic compounds, as Pb; BEI

Additional information:

PEL = Permissible Exposure Limit (OSHA)
TLV= Threshold Limit Value (ACGIH)
OSHA= Occupational Safety and Health Administration
ACGIH= American Conference of Governmental Industrial Hygienists

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.

(Contd. on page 5)

Trade name: FL250D Solder Paste Sn63Pb37 Alloy

(Contd. of page 4)

Breathing equipment:

When ventilation is not sufficient to remove fumes from the breathing zone, a safety approved respirator or self-contained breathing apparatus should be worn.

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:

Protective gloves

Material of gloves:

Nitrile rubber, NBR

Natural rubber, NR

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Safety glasses



Face Shield with Safety Glasses when refilling.

9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Pasty
Color: Silver grey
Odor: Mild

pH-value: Not determined.

Change in condition

Melting point/Melting range: > 100 °C (> 212 °F)
Undetermined.

Flash point: > 93 °C (> 199 °F)

Auto igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Density: Not determined.

Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

Solvent content:

Organic solvents: 3.2 %

Solids content: 96.5 %

10: STABILITY AND REACTIVITY

10.1 Reactivity No further relevant information available.

(Contd. on page 6)

Trade name: FL250D Solder Paste Sn63Pb37 Alloy

(Contd. of page 5)

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: Strong acids, strong oxidizers.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

When heated to soldering temperatures, the solvents are evaporated and rosin may be thermally degraded to liberate aliphatic aldehydes and acids.

11: TOXICOLOGICAL INFORMATION**11.1 Information on toxicological effects****Acute toxicity:**

Harmful if swallowed.

LD/LC50 values that are relevant for classification:**Rosin**

Oral	LD50	> 4000 mg/kg (Rat)
Dermal	LD50	>2500 mg/kg (rabbit)

Primary irritant effect:

on the skin: Possible local irritation by contact with flux or fumes.

on the eye: Smoke during soldering can cause eye irritation.

through inhalation:

Flux fumes during soldering may cause irritation and damage of mucous membranes and respiratory system.

through ingestion: May be harmful if swallowed.

Sensitization:

May cause an allergic skin reaction.

Additional toxicological information:**Carcinogenic categories****IARC (International Agency for Research on Cancer)**

7439-92-1	LEAD (Pb)	2B
-----------	-----------	----

NTP (National Toxicology Program)

7439-92-1	LEAD (Pb)	R
-----------	-----------	---

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12: ECOLOGICAL INFORMATION**12.1 Toxicity**

Aquatic toxicity: No further relevant information available.

Additional ecological information:**General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

The product contains heavy metals. Avoid transfer into the environment. Specific preliminary treatments are necessary

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

US
(Contd. on page 7)



SAFETY DATA SHEET (SDS)
According to 1907/2006/EC, Article 31

Version number 10

Reviewed on 12/01/2015

Trade name: FL250D Solder Paste Sn63Pb37 Alloy

(Contd. of page 6)

13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Recommendation:

Disposal must be made according to official regulations.
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

14: TRANSPORT INFORMATION

14.1 UN-Number

DOT, ADR, ADN, IMDG, IATA Not applicable

14.2 UN proper shipping name

DOT, ADR, ADN Not applicable
IMDG, IATA Not applicable
Not regulated

14.3 Transport hazard class(es)

DOT, ADR, ADN, IMDG, IATA
Class Not applicable

14.4 Packing group

DOT, IMDG, IATA Not applicable
Marine pollutant: No

14.6 Special precautions for user Not applicable.

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

UN "Model Regulation": Not applicable.

15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

All ingredients are listed on the following Government Inventories:

- China: Inventory of Existing Chemical Substances in China (IECSC)
- Korea: Korea Existing Chemicals List (ECL)
- Europe: European Inventory of Existing Commercial Chemical Substances (EINECS)
- Japan: Inventory of Existing and New Chemical Substances (ENCS)
- Philippines: Philippine Inventory of Chemicals and Chemical Substances (PICCS)
- USA: TSCA (Toxic Substances Control Act) TSCA Inventory of Chemical Substances

USA The following information relates to product regulation specific to the USA.

SARA (Superfund Amendments and Reauthorization Act)

Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

7439-92-1 | LEAD (Pb)

TSCA (Toxic Substances Control Act): Kester certifies that all components listed below for the subject finished product are on the TSCA Inventory of Chemical Substances and are not subject to any chemical specific regulation under TSCA Section 12(b) export notification requirements delineated at 40 CFR part 707, subpart D.

All ingredients are listed or exempt from listing.

(Contd. on page 8)

Trade name: FL250D Solder Paste Sn63Pb37 Alloy

(Contd. of page 7)

California Proposition 65**Chemicals known to cause cancer:**

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

LEAD (Pb)

diethanolamine

tert-butyl-4-methoxyphenol

Chemicals known to cause reproductive toxicity:

WARNING: This product contains a chemical(s) known to the State of California to cause birth defects and/or other reproductive harm.

LEAD (Pb)

N-methyl-2-pyrrolidone

Carcinogenic categories**EPA (Environmental Protection Agency)**

7439-92-1 | LEAD (Pb)

B2

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

CANADA:

Not classified.

Workplace Hazardous Materials Identification (WHMIS):

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR) and the Safety Data Sheet (SDS) contains all of the information required by the CPR.

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labeled according to the CLP regulation.

Hazard pictograms

GHS07 GHS08

Signal word Danger**Hazard-determining components of labeling:**

LEAD (Pb)

Rosin

Rosin

Halogenated organic diol

Hazard statements

Harmful if swallowed.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

In case of inadequate ventilation wear respiratory protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

IF ON SKIN: Wash with plenty of water.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

(Contd. on page 9)

Trade name: FL250D Solder Paste Sn63Pb37 Alloy

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 8)

16: OTHER INFORMATION

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Material Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Material Safety Data Sheet as a source for hazard information.

Department issuing Safety Data Sheet (SDS): Product Compliance / EHS Department

Contact: EHS_Kester@kester.com

Date of preparation / last revision 12/01/2015 / 9

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1B

Carc. 1B: Carcinogenicity, Hazard Category 1B

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 1B: Reproductive toxicity, Hazard Category 1B

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

* **Data compared to the previous version altered.**