

5560

Solder-Nu Metal Cleaner

For Solder and Silver

Product Description

Kester 5560 Solder-Nu is a non-fuming liquid solution for removing oxides, sulfides, carbonates and other contamination, such as etch residues, from copper metal surfaces to facilitate soldering. This stable solution cleans by dissolving or solubilizing the contamination for easy removal by water rinsing. The chemical cleaning action is quite different from strong mineral acids which etch away valuable base metal and passivate the surface by insoluble film formation. Kester 5560 contains a pink pH indicator which turns yellow at pH 3.5 indicating the solution has lost its efficiency. Kester 5560 is a non-foaming chemical for use in spray cleaning equipment. Because the etch rate is controlled, the bath life is very extended. Kester 5560 will selectively remove surface contamination from solder-plated or tin-plated surfaces as well as very tarnished copper surfaces. Kester 5560 is very effective in cleaning silver-plated surfaces with no appreciable metallic etching.

Performance Characteristics:

- Removes oxidation to facilitate soldering
- Easily cleaned in water
- Minimal Etching

Physical Properties

Specific Gravity: 1.085 ± 0.010

Antoine Paar DMA 35 @ 25°C

pH (10% solution): 1.0

Hanna Instruments 8314 @ 25°C

Flash Point: >100°C (212°F)

Application Notes

Surfaces to be cleaned should be free of oil and grease. Kester 5560 should be used as received in plastic or glass containers at room temperature or hot 49-60°C (120-140°F). Heating the solution accelerates the rate at which Kester 5560 Solder-Nu reacts with contaminants. Parts are immersed for 30 seconds to 3 minutes depending on the condition of the surface and then water-rinsed to remove the solubilized contamination. Residual water-insoluble metallic complexes can be removed from an etched surface with minimal etching of the metal. Plating or etching residues can seriously affect the reliability of a soldered connection.

Cleaning:

No neutralizer, saponifiers or detergents are necessary in the water wash system for complete removal of residues. It is not recommended to use high mineral content tap water. Otherwise, tap, deionized or softened water may be used for cleaning.

Storage and Shelf Life:

Because this formulation is water based, it is subject to freezing. A minimum storage temperature of 4°C (40°F) is recommended. If frozen, the Kester 5560 is easily reconstituted by stirring at room temperature. Shelf life is 2 years from date of manufacture when handled properly and held at 4-25°C (40-77°F).

Health & Safety:

This product, during handling or use, may be hazardous to health or the environment. Read the Material Safety Data Sheet and warning label before using this product.

World Headquarters: 800 West Thorndale Avenue, Itasca, Illinois, 60143-1341 USA
Phone: (+1) 847-297-1600 • **Email:** customerservice@kester.com • **Website:** www.kester.com

Asia Pacific Headquarters
500 Chai Chee Lane
Singapore 469024
(+65) 6449-1133
customerservice@kester.com.sg

European Headquarters
Zum Plom 5
08541 Neuensalz
Germany
(+49) 3741 4233-0
customerservice@kester-eu.com

Japanese Headquarters
20-11 Yokokawa 2-Chome
Sumida-Ku
Tokyo 130-0003 Japan
(+81) 3-3624-5351
jpsales@kester.com.sg

The data recommendations presented are based on tests, which we consider reliable. Because Kester has no control over the conditions of use, we disclaim any responsibility connected with the use of any of our products or the information presented. We advise that all chemical products be used only by or under the direction of technically qualified personnel who are aware of the potential hazards involved and the necessity for reasonable care in their handling. The technical information contained herein is consistent with the properties of this material but should not be used in the preparation of specifications as it is intended for reference only. For assistance in preparing specifications, please contact your local Kester office for details.