

KESTER® 5760 NEUTRALIZER

For Removing Residues from Fluxes

DESCRIPTION

Kester 5760 Neutralizer is a buffered, alkaline concentrated formula which effectively removes both organic and inorganic acid flux residues. This includes water soluble fluxes used in wave soldering, hot air leveling and infrared reflow processes. Simple neutralization with caustic soda or other alkaline solutions will not completely remove ionizable, potentially corrosive and conductive residue which is formed during soldering. 5760 will completely solubilize chloride complex residues such as lead chloride by selective chelation so that a water rise will remove all traces of harmful contamination.

READ ENTIRE TECHNICAL DATA SHEET BEFORE USING THIS PRODUCT

FEATURES & BENEFITS

- Removes ionizable residues
- Easily cleaned in water
- Effective for both organic and inorganic residues

ROHS COMPLIANCE

This product meets the requirements of the Restriction of Hazardous Substances (RoHS) Directive, 2015/863 for the stated banned substances.

TECHNICAL DATA

Category	Results	Procedure/Remarks
Physical Properties		
Specific Gravity	1.200	Anton Paar DMA 35 @ 25 °C

APPLICATION

When diluted to make a 2 to 10% solution with water, 5760 is used as an initial wash followed by a thorough water rinse to ensure complete removal of 5760 and dissolved flux residues. The blue color of the solution is a concentration indicator which will fade as the solution weakens. Fresh 5760 may be added to the solution to maintain a constant indicator color. When the solution becomes cloudy, it should be replaced. Parts are immersed for 15 seconds to 2 minutes in 5760 depending on the nature of the residue, part configuration and the length of time between soldering and cleaning, followed by a clean water rise.

PROCESSING GUIDELINES

Cleaning

No neutralizer, saponifiers or detergents are necessary in the water wash system for complete removal of residues. It is not recommended to use high mineral content tap water. Otherwise, tap, deionized or softened water may be used for cleaning. Generally in-line spray cleaners should incorporate a gross prewash (to drain) to remove the flux residue prior to washing in 5760.

Storage, Handling and Shelf Life

Shelf life is 3 years from the date of manufacture when appropriately handled and held at 4 to 25 °C (40 to 77 °F). 5760 is water-based, and the minimum storage temperature of 4 °C (40 °F) is recommended to prevent freezing. If frozen, stir or shake the container at room temperature before use to reconstitute.

Over time, it is typical for the dye to come out of the solution as black/brown particles. This does not impact the overall performance of the product.

SAFETY & WARNING

It is recommended that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use. **Safety Data Sheets are available.**

CONTACT INFORMATION

www.macdermidalpha.com

North America 140 Centennial Avenue Piscataway, NJ 08854 1.800.367.5460	Europe Unit 2, Genesis Business Park Albert Drive Woking, Surrey, GU21 5RW, UK 44.01483.758400	Asia 8/F., Two Sky Parc 51 Hung To Road Kwun Tong, Kowloon, Hong Kong, SAR China 852.2500.5365
---	---	--

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product. READ IT THOROUGHLY PRIOR TO PRODUCT USE. Emergency safety directory assistance: US 1 202 464 2554, Europe + 44 1235 239 670, Asia + 65 3158 1074, Brazil 0800 707 7022 and 0800 172 020, Mexico 01800 002 1400 and (55) 5559 1588

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any noncompliant product at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct, indirect, incidental or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect, incidental and consequential damages that may result from use of the products under such conditions, and agrees to exonerate, indemnify, defend and hold harmless MacDermid, Incorporated and its affiliates therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in a manner that infringes any patent or other intellectual property rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

© 2019 MacDermid, Inc. and its group of companies. All rights reserved. "(R)" and "TM" are registered trademarks or trademarks of MacDermid, Inc. and its group of companies in the United States and/or other countries.