

# **KESTER® 817 SOLDERING FLUX**

## **Inorganic Acid Fluxes**

## **DESCRIPTION**

Kester 817 Soldering Flux is an inorganic acid flux. Inorganic fluxes are solutions of inorganic salts for use as general all-purpose fluxes. These fluxes are active formulations for soldering difficult-to-solder metals. The Inorganic Acid Fluxes were developed for non-electronic soldering applications and provide maximum wetting, leaving residues which can be removed with water. The corrosive nature of the residues precludes their use for electrical or electronic applications. Flux residues should be carefully removed to prevent corrosion caused by residual chloride salts. All formulations can be used for soldering with an iron, torch, oven induction coils or resistance tools.

Although this is a mild flux, it is a very active solution developed for soldering nickel-chrome and stainless steel alloys where regular acid fluxes are not active enough to remove the resistant oxide coatings.

817 is classified as INH1 per IPC J-STD-004.

#### READ ENTIRE TECHNICAL DATA SHEET BEFORE USING THIS PRODUCT

## **ROHS COMPLIANCE**

This product meets the requirements of the Restriction of Hazardous Substances (RoHS) Directive. 2015/863 for the stated banned substances.

#### **TECHNICAL DATA**

Category	Results	Procedure/Remarks
Physical Properties		
Specific Gravity	1.422 ± 0.015	
Percent Solids	43.3	
Flash Point	None	
Appearance	Clear, colorless to light yellow liquid	





# **TECHNICAL DATA SHEET**

## **PROCESSING GUIDELINES**

## Cleaning

All inorganic fluxes have the potential to form water insoluble, chloride complex residues such as lead chloride. Kester 5760 Neutralizer will solubilize these residues for complete removal with water. Complete removal of residues left when soldering with 817 can be assured by rinsing with a 1% solution of hydrochloric acid. This should be followed by a rinse with a 2 to 10% solution of 5760 Neutralizer and a final rinse with clean water.

## Storage, Handling and Shelf Life

Shelf life is 3 years from the date of manufacture when handled properly and held at 10 to 25  $^{\circ}$ C (50 to 77  $^{\circ}$ F).

#### **RECYCLING SERVICES**

We provide safe and efficient recycling services to help companies meet their environmental and legislative requirements and at the same time, maximize the value of their waste streams.

Our service collects solder dross, solder scrap, and various forms of solder paste waste. Please contact your local sales representative for recycling capabilities in your area.





Issue: 19 January 2022



# **TECHNICAL DATA SHEET**

### **SAFETY & WARNING**

It is recommended that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use. **Safety Data Sheets are available.** 

### **CONTACT INFORMATION**

#### www.macdermidalpha.com

North America 140 Centennial Avenue Piscataway, NJ 08854 1.800.367.5460 **Europe**Unit 2, Genesis Business Park
Albert Drive
Woking, Surrey, GU21 5RW, UK
44.01483.758400

Asia 8/F., Two Sky Parc 51 Hung To Road Kwun Tong, Kowloon, Hong Kong, SAR China 852.2500.5365

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product. READ IT THOROUGHLY PRIOR TO PRODUCT USE. Emergency safety directory assistance: US 1 202 464 2554, Europe + 44 1235 239 670, Asia + 65 3158 1074, Brazil 0800 707 7022 and 0800 172 020, Mexico 01800 002 1400 and (55) 5559 1588

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY (SI MADE. The following warrantpi s made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any noncompliant product at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct, indicert, incidental or consequential, arising out of the inability to use the product. Notwithshiding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect, incidental and consequential damages that may result from use of the products under such conditions, and agrees to exonerate, indemnify, defend and hold harmless MacDemid, Incorporated and its affiliates therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in a manner that infringes any patent or other intellectual property rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

© 2019 MacDermid, Inc. and its group of companies. All rights reserved. "(R)" and "TM" are registered trademarks or trademarks of MacDermid, Inc. and its group of companies in the United States and/or other countries.



Issue: 19 January 2022